
BookletChart


Southern Dall Island and Vicinity

(NOAA Chart 17409)




A reduced scale NOAA nautical chart for small boaters. When possible, use the full size NOAA chart for navigation.

- ☑ Complete, reduced scale nautical chart
- ✓ Print at home for free
- ☑ Up to date with all Notices to Mariners
- ☑ United States Coast Pilot excerpts
- ✓ Compiled by NOAA, the nation's chartmaker.



Home Edition (not for sale)



What are Nautical Charts?

Nautical charts are a fundamental tool of marine navigation. They show water depths, obstructions, buoys, other aids to navigation, and much more. The information is shown in a way that promotes safe and efficient navigation. Chart carriage is mandatory on the commercial ships that carry America's commerce. They are also used on every Navy and Coast Guard ship, fishing and passenger vessels, and are widely carried by recreational boaters.

What is a BookletChart[™]?

This BookletChart is made to help recreational boaters locate themselves on the water. It has been reduced in scale for convenience, but otherwise contains all the information of the full-scale nautical chart. The bar scales have also been reduced, and are accurate when used to measure distances in this BookletChart. See the Note at the bottom of page 5 for the reduction in scale applied to this chart.

Whenever possible, use the official, full scale NOAA nautical chart for navigation. Nautical chart sales agents are listed on the Internet at http://www.NauticalCharts.NOAA.gov.

This BookletChart does NOT fulfill chart carriage requirements for regulated commercial vessels under Titles 33 and 44 of the Code of Federal Regulations.

Notice to Mariners Correction Status

This BookletChart has been updated for chart corrections published in the U.S. Coast Guard Local Notice to Mariners, the National Geospatial Intelligence Agency Weekly Notice to Mariners, and, where applicable, the Canadian Coast Guard Notice to Mariners. Additional chart corrections have been made by NOAA in advance of their publication in a Notice to Mariners. The last Notices to Mariners applied to this chart are listed in the Note at the bottom of page 7. Coast Pilot excerpts are not being corrected.



[Coast Pilot 8, Chapter 6 excerpts]

(19) Chickwan Bight, about 2.5 miles W of Cape Muzon, is open and exposed and has depths of about 30 fathoms at the entrance, decreasing to 12 fathoms near the head.
(20) Wolk Harbor, about 3.5 miles W of Cape Muzon, is deep throughout and is open and exposed. Midchannel depths are 20 to 40 fathoms. There are tide rips off Wolk Point between Chickwan Bight and Wolk Harbor.
(21) Liscome Bay, about 4.3 miles WNW of

Cape Muzon, affords an anchorage for small vessels, but is exposed to S weather and swell. A submerged rock is about 100 yards off the E shore, about 1.1 miles within the entrance, where the bay narrows. A small rock is about 230 yards N of the submerged rock.

(22) **Point Cornwallis**, marked by a light, is a prominent headland about 6.6 miles WNW of Cape Muzon. At the extremity is a projecting rocky

- point, 195 feet high, on the N side of which, close-to, is a similar point, 131 feet high, near which are two small rocks. A rock awash is immediately W of the projecting point, and a submerged rock and a bare rock are about 0.3 mile to the SE. Immediately back of the point is a round-topped hill, 440 feet high. **Stripe Mountain**, about 1.3 miles NE of the point, is marked by a prominent slide on the NW side.
- (24) **Essowah Harbor** is about 1.7 miles NNW from Security Cove. The entrance channel is about 0.3 mile long and 30 yards wide; there are two rocks near the entrance. **Essowah Lakes** empty into the head of Essowah Harbor. A small lake, 0.5 mile S of Essowah Lakes, empties near the entrance to Essowah Harbor.
- (25) **Parrot Rock** is about 0.9 mile WNW from **Essowah Point**, the point S of the entrance to Essowah Harbor, and is about 0.2 mile offshore.
- (26) **Port Bazan** (54°48.8'N., 132°58.5'W.) is between two prominent mountain peaks, about 15 miles from Cape Muzon and 7.5 miles NW of Point Cornwallis. The NW mountain top is a small bare tip; the SE mountain is roughly the shape of a rounded cone, and is heavily wooded to the top.
- (27) **Dolgoi Island**, at the entrance to Port Bazan is mound shaped and wooded (with the seaward side rocky and bare of vegetation) to heights of 50 to 100 feet. There are through channels to the NW and SE. W from Dolgoi Island, on the S side of the entrance to the N channel, is a group of four islets close together.
- (77) The N side of Cape Muzon trends NW for about 2.5 miles, forming the S side of **McLeod Bay**. **Little Daykoo Harbor**, a small-boat harbor, is close N of McLeod Bay.
- (78) **Daykoo Islands** and **Datzkoo Islands** extend 2 miles in a N direction from McLeod Bay, with a maximum distance of about 1 mile offshore.
- (79) **Long Island** forms the W side of Cordova Bay for a distance of about 12 miles. The E shore of the island is rugged and broken, with a number of outlying islets and rocks within a distance of about 0.5 mile. There are also a number of indentations and some anchorages.
- (82) **Coning Inlet** is on the E side of Long Island about 4.5 miles from the S end. It is open to E and does not afford good anchorage. A lagoon is at the head of the inlet, where it is connected by saltwater rapids.
- (83) **Nina Cove**, on the S side of Coning Inlet at the entrance, affords secure anchorage for small craft in 3 to 4 fathoms, sticky bottom. The anchorage is about 200 yards in extent and is S of the small islet in the center of the cove at its head.
- (86) **Natoma Point**, low and wooded, is the N point at the entrance to Natoma Bay. A large wooded, high-water islet is close off the point to S. Give the E side of the point and islet a berth of about 0.3 mile.
- (168) **Kaigani Point**, at the SW end of Long Island, is low and wooded. A large rock, 18 feet high, is 0.7 mile NW of Kaigani Point and about 0.2 mile offshore.
- (169) **Datzkoo Harbor** is on the E side of Dall Island about 1.6 miles NW of the Datzkoo Islands. The entrance is clear and is N of two wooded islands. Anchorage can be had in 15 to 20 fathoms, soft bottom.
- (170) **South Kaigani Harbor**, immediately N of Datzkoo Harbor, is constricted at the entrance by reefs on the N side and a rock that uncovers 5 feet on the S side. The channel about 100 yards wide has a depth of 4½ fathoms. During the fishing season a fish-buying scow may be anchored in the harbor. The scow sells gasoline, diesel fuel, water, provisions and fishing supplies.
- (171) **North Kaigani Harbor**, immediately N of South Kaigani Harbor, is entirely exposed to SE weather and the ocean swell, and is of no use as an anchorage.
- (173) **Pond Bay** is on the SW side of Kaigani Strait about 3.5 miles N of North Kaigani Harbor. A wooded island is halfway toward the head of the bay with a clear channel on the N side. Anchorage may be had W of this island in desired depths up to 20 fathoms, soft bottom. However, a strong wind blows up the bay in SE weather and, because of the danger from dragging, it is not recommended for anchorage.

Corrected through NM Aug. 3/02 Corrected through LNM Jul. 9/02

HEIGHTS

Heights in feet above Mean High Water.

CAUTION

Temporary changes or defects in aids to navigation are not indicated on this chart. See Local Notice to Mariners.

Mercator Projection

Scale 1:40,000 at Lat 54° 45' North American Datum of 1983 (World Geodetic System 1984) SOUNDINGS IN FATHOMS AT MEAN LOWER LOW WATER

VESSEL TRAFFIC SERVICES

Traffic services calling-in point with number; arrows indicate direction of vessel movement. For additional information, see Sailing Directions.

WARNING

The prudent mariner will not rely solely on any single aid to navigation, particularly on floating aids. See U.S. Coast Guard Light List and U.S. Coast Pilot for details.

SUPPLEMENTAL INFORMATION

Consult U.S. Coast Pilot 8 for important supplemental information.

NOAA WEATHER RADIO BROADCASTS

The NOAA Weather Radio stations listed The NOAA Weather Hadio stations listed below provide continuous weather broadcasts. The reception range is typically 20 to 40 nautical miles from the antenna site, but can be as much as 100 nautical miles for stations at high elevations.

Mt. McArthur, AK	KZZ-95	162.525 MHz
Sukkwan I, AK	KZZ-89	162.425 MHz
Zarembo I, AK	KZZ-91	162.450 MHz
Gravina I, AK	KZZ-96	162.525 MHz
Duke I, AK	KZZ-92	162.450 MHz
Craig, AK	KXI-80	162.475 MHz
Ketchikan, AK	WXJ-26	162.55 MHz

AIDS TO NAVIGATION

Consult U.S. Coast Guard Light List for supplemental information concerning aids to navigation.

NOTE A

NOTE A

Navigation regulations are published in Chapter 2, U.S. Coast Pilot 8. Additions or revisions to Chapter 2 are published in the Notice to Mariners. Information concerning the regulations may be obtained at the Office of the Commander, 17th Coast Guard District in Juneau, Alaska, or at the Office of the District Engineer, Corps of Engineers in Anchorage, Alaska.

Refer to charted regulation section numbers.

Refer to charted regulation section numbers.

POLLUTION REPORTS

Report all spills of oil and hazardous sub-stances to the National Response Center via 1-800-424-8802 (toll free), or to the nearest U.S. Coast Guard facility if telephone communication is impossible (33 CFR 153).

HORIZONTAL DATUM

The horizontal reference datum of this chart is North American Datum of 1983 (NAD 83), which is Norm American Datum or 1982 (NAU 83), while for charting purposes is considered equivalent to the World Geodetic System 1984 (WGS 84). Geographic positions referred to the North American Datum of 1927 must be corrected an average of 1.242* southward and 5.991* westward to agree with this chart.

LOCAL MAGNETIC DISTURBANCE
Differences of as much as 4" from the normal variation
have been observed at Cape Muzon, 3" in the Daykoo
Islands, and 4" in Kalgani Strait about 1.2 miles NW of Kalgani

SOURCE DIAGRAM \ \ \ \ \ \ (((

The outlined areas represent the limits of the most recent hydrographic survey information that has been evaluated for charting. Surveys have been banded in this diagram by date and type of survey. Channels maintained by the U.S. Army Corps of Engineers are periodically resurveyed and are not shown on this diagram. Refer to Chapter 1, <u>United States Coast Pilot.</u>

AUTHORITIES

Hydrography and topography by the National Ocean Service, Coast Survey with additional data from the Department of Agriculture and U.S. Coast Guard.

Table of Selected Chart Notes

COLREGS, 80.1705 (see note A) International Regulations for Preventing Collisions at Sea, 1972.
The entire area of this chart falls seaward of the COLREGS Demarcation Line.

This nautical chart has been designed to promote safe navigation. The National Ocean Service encourages users to submit corrections, additions, or comments for improving this chart to the Chief, Marine Chart Division (N/CS2), National Ocean Service, NOAA, Silver Spring, Maryland 20910-3282.

		IDAL IN OIL	777 111011		
Place		Height referred to datum of soundings (MLLW)			
Name	(LAT/LONG)	Mean Higher High Water	Mean High Water	Mean Low Water	Extreme Low Water
		feet	feet	feet	feet
Security Cove	(54°45'N/132°51W)	10.8	10.1	1.4	-4
Cape Muzon	(54°40'N/132°40'W)	12.1	11.3	1.4	-4
Kaigani Harbor	(54°45'N/132°43'W)	11.9	11.3	1.5	-4
American Bay	(54°51'N/132°50'W)	12.4	11.6	1.4	-4

ABBREVIATIONS (For complete list of Symbols and Abbreviations, see Chart No. 1.)

Aids to Navigation (lights a	are white unless ot	herwise indicated):		
AERO aeronautical Al alternating B black	lso isoph		Mo morse code N nun OBSC obscured	R TR radio tower Rot rotating s seconds
Bn beacon C can DIA diaphone F fixed FI flashing	LT HO li M nautic m minute MICRO T Mkr mark	al mile es R microwave tower	Oc occulting Or orange Q quick R red Ra Ref radar reflector	SEC sector St M statute miles VQ very quick W white WHIS whistle
Bottom characteristics:			R Bn radiobeacon	Y yellow
Bids boulders bk broken Cy clay	Co coral G gravel Grs grass	gy gray h hard M mud	Oys oysters Rk rock S sand	so soft Sh shells sy sticky
Miscellaneous: AUTH authorized	Obstn	obstruction	PD position doubtful	Subm submerged

CD existence doubtful PA position approximate Per position doubtful PA position approximate Rep reported 2.1. Wreck, rock, obstruction, or shoal swept clear to the depth indicated.

(2) Rocks that cover and uncover, with heights in feet above datum of soundings.

AUTHORITIES

Hydrography and topography by the National Ocean Service, Coast Survey with additional data from the Department of Agriculture and U.S. Coast Guard.



AIDS TO NAVIGATION

Consult U.S. Coast Guard Light List for supplemental information concerning aids to navigation.


WARNING

The prudent mariner will not rely solely on any single aid to navigation, particularly on floating aids. See U.S. Coast Guard Light List and U.S. Coast Pilot for details.

TIDAL INFORMATION

	Place	Height ref	erred to datun	n of sounding	s (MLLV
Name	(LAT/LONG)	Mean Higher High Water	Mean High Water	Mean Low Water	Extrer Low W
		feet	feet	feet	feet
Security Cove	(54°45'N/132"51W)	10.8	10.1	1.4	-4
Cape Muzon	(54°40'N/132°40'W)	12.*	11.3	1.4	-4
Kaigani Harbor	(54°45'N/132°43'W)	11.9	11.3	1.5	-4
American Bay	(54"51'N/132"50'W)	12.4	11.6	1.4	-4

(602)









UNITED STATES

ALASKA - SOUTHEAST COAS

POLLUTION REPORTS

Report all spills of oil and hazardous substances to the National Response Center via 1-800-424-8802 (toll free), or to the nearest L.S. Coast Guard tacillity if telephone communication is impossible (33 CFR 153).

HORIZONTAL DATUM


LW)

The hor zontal reference datum of this chart is North American Datum of 1983 (NAD 83), which for charting purposes is considered equivalent to the World Geodetic System 1984 (WGS 84). Geographic positions referred to the North American Datum of 1927 must be corrected an average of 1-22" southward and 5-991" westward to agree with this chart.

SOUTHERN DALL ISLAND

Mercator Projection Scale 1:40,000 at Lat 54° 45' North American Datum of 1983 (World Geodetic System 1984) SOUNDINGS IN FATHOMS AT MEAN LOWER LOW WATER

Formerly C&GS 8146, 1st Ed., Sept. 1924 KAPP 2728



This BookletChart was reduced to 75% of the original chart scale. The new scale is 1:53333. Barscales have also been reduced and are accurate when used to measure distances in this BookletChart.





UNITED STATES

KA - SOUTHEAST COAST

L ISLAND AND VICINITY

Mercator Projection cale 1:40,000 at Lat 54° 45' orth American Datum of 1983 (World Geodetic System 1984) SOUNDINGS IN FATHOMS AT MEAN LOWER LOW WATER

NOTE A

NOTE A

Navigation regulations are published in Chapter 2, U.S. Coast Pilot 8. Additions or revisions to Chapter 2 are published in the Notice to Mariners. Information concerning the regulations may be obtained at the Office of the Commander, 17th Coast Guard District in Juneau, Alaska, or at the Office of the District Engineer, Corps of Engineers in Anchorage, Alaska.

Refer to charted regulation section numbers.

Refer to charted regulation section numbers.

ABBREVIATIONS (For complete li Alds to Navigation (lights are white un


AERO aeronautical Al alternating B black Bn beacon C can DIA diaphone FI flashing

Bottom characteristics:


Bids boulders bk broken Cy clay G gravel Grs gras

Miscellaneous: AUTH authorized

ED existence doubtful [21, Wreck, rock, obstruction, (2) Rocks that cover and unc







e lis: of Symbols and Abbreviations, see Chart No. 1.)

N nun

OBSC obscured

Ra Ref radar reflector

Oc occulting Or orange O quick R red

\$ sand

Rot rotating

SEC sector St M statute miles VQ very quick W white

WHIS whistle

sy sticky

Subm submerged

s seconds

IQ interrupted quick Iso isophase

LT HO lighthouse
M nautical mile
m minutes
MICRO TR microwave to

gy gray h hard M mud

oral ivol irass Obstn obstruction

PD position doubtful PA position approximate Rep reported n, or shoal swept clear to the depth indicated. Incover, with heights in feet above datum of soundings CAUTION

Temporary changes or defects in aids to navigation are not indicated on this chart. See Local Notice to Mariners.

SUPPLEMENTAL INFORMATION Consult U.S. Coast Pilot 8 for important supplemental information

HEIGHTS Heights in feet above Mean High Water


NOAA WEATHER RADIO BROADCASTS


The NOAA Weather Radio stations listed below provide continuous weather broadcasts. The reception range is typically 20 to 40 nautical miles from the antenna site, but can be as much as 100 nautical miles for stations at

Mt. McArthur, AK KZZ-95 162.525 MHz KZZ-89 KZZ-91 KZZ-96 162 425 MHz Zarembo I, AK Gravina I, AK Duke I, AK 162.450 MHz 162.525 MHz 162.450 MHz KZZ-92 Craig, AK KXI-80 162.475 MHz 162.55 MI Iz

SOUNDINGS IN FATHOMS


Nautical Chart Catalog No. 3, Panels Q, R

































. The Nationa comments for ational Ocean

SOUNDINGS IN FATHOMS

Published at Washington, D.C.
U.S. DEPARTMENT OF COMMERCE
NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRA
NATIONAL OCEAN SERVICE
COAST SURVEY




Published at Washington, D.C.
DEPARTMENT OF COMMERCE
EANIC AND ATMOSPHERIC ADMINISTRATION
NATIONAL OCEAN SERVICE
COAST SURVEY

FAIHOMS	1
FEET	5
METERS	angan baa

4 Nor

Printed at reduced scale.		S C /	SCALE 1:40,000 Nautical Miles		See Note on page 5.			
. 1	1/2	0		1 Yards		2		3
	1000	0	1000	2000	3000	4000	5000	



EMERGENCY INFORMATION

VHF Marine Radio channels for use on the waterways:

Channel 6 – Inter-ship safety communications.

Channel 9 – Communications between boats and ship-to-coast.

Channel 13 – Navigation purposes at bridges, locks, and harbors.

Channel 16 – Emergency, distress and safety calls

to Coast Guard and others, and to initiate calls to other vessels. Contact the other vessel, agree to another channel, and then switch.

Channel 22A – Calls between the Coast Guard and the public. Severe weather warnings, hazards to navigation and safety warnings are broadcast here.

Channels 68, 69, 71, 72 & 78A – Recreational boat channels.

Distress Call Procedures

- 1. Make sure radio is on.
- 2. Select Channel 16.
- 3. Press/Hold the transmit button.
- 4. Clearly say: "MAYDAY, MAYDAY, MAYDAY."
- Also give: Vessel Name and/or Description; Position and/or Location; Nature of Emergency; Number of People on Board.
- 6. Release transmit button.
- Wait for 10 seconds If no response Repeat MAYDAY Call.

HAVE ALL PERSONS PUT ON LIFE JACKETS!!

Mobile Phones – Call 911 for water rescue.

Coast Guard Search & Rescue (Pacific Coord) – 510-437-3700

Coast Guard Search & Rescue (RCC Juneau) – 907-463-2000

<u>NOAA Weather Radio</u> – 162.400 MHz, 162.425 MHz, 162.450 MHz, 162.475 MHz, 162.500 MHz, 162.525 MHz, 162.550 MHz.

Getting and Giving Help – Signal other boaters using visual distress signals (flares, orange flag, lights, arm signals); whistles; horns; and on your VHF radio. You are required by law to help boaters in trouble. Respond to distress signals, but do not endanger yourself.



NOAA CHARTING PUBLICATIONS

Official NOAA Nautical Charts – NOAA surveys and charts the national and territorial waters of the U.S, including the Great Lakes. We produce over 1,000 traditional nautical charts covering 3.4 million square nautical miles. Carriage of official NOAA charts is mandatory on the commercial ships that carry our commerce. They are used on every Navy and Coast Guard ship, fishing and passenger vessels, and are widely carried by recreational boaters. NOAA charts are available from official chart agents listed at: www.NauticalCharts.NOAA.gov.

Official Print-on-Demand Nautical Charts — These full-scale NOAA charts are updated weekly by NOAA for all Notice to Mariner corrections. They have additional information added in the margin to supplement the chart. Print-on-Demand charts meet all federal chart carriage regulations for charts and updating. Produced under a public/private partnership between NOAA and OceanGrafix, LLC, suppliers of these premium charts are listed at www.OceanGrafix.com.

Official Electronic Navigational Charts (NOAA ENCs®) -

ENCs are digital files of each chart's features and their attributes for use in computer-based navigation systems. ENCs comply with standards of the International Hydrographic Organization. ENCs and their updates are available for free from NOAA at www.NauticalCharts.NOAA.gov.

Official Raster Navigational Charts (NOAA RNCs[™]) –

RNCs are geo-referenced digital pictures of NOAA's charts that are suitable for use in computer-based navigation systems. RNCs comply with standards of the International Hydrographic Organization. RNCs and their updates are available for free from NOAA at www.NauticalCharts.NOAA.gov.

Official BookletCharts[™] – BookletCharts[™] are reduced scale NOAA charts organized in page-sized pieces. The "Home Edition" can be downloaded from NOAA for free and printed. The Internet address is www.NauticalCharts.gov/bookletcharts.

Official PocketChartsTM – PocketChartsTM are for beginning recreational boaters to use for planning and locating, but not for real navigation. Measuring a convenient 13" by 19", they have a 1/3 scale chart on one side, and safety, boating, and educational information on the reverse. They can be purchased at retail outlets and on the Internet.

Official U.S. Coast Pilot® – The Coast Pilots are 9 text volumes containing information important to navigators such as channel descriptions, port facilities, anchorages, bridge and cable clearances, currents, prominent features, weather, dangers, and Federal Regulations. They supplement the charts and are available from NOAA chart agents or may be downloaded for free at www.NauticalCharts.NOAA.gov.

Official On-Line Chart Viewer – All NOAA nautical charts are viewable here on-line using any Internet browser. Each chart is up-to-date with the most recent Notices to Mariners. Use these on-line charts as a ready reference or planning tool. The Internet address is www.NauticalCharts.gov/viewer.

Official Nautical Chart Catalogs – Large format, regional catalogs are available for free from official chart agents. Page size, state catalogs are posted on the Internet and can be printed at home for free. Go to http://NauticalCharts.NOAA.gov/mcd/ccatalogs.htm.

Internet Sites: www.Noa.gov, <a href="